

1106749

# SAFETY THERMOSTAT 230° SINGLE PHASE 0,5A - SENSOR Ø 4X116mm CAPILLARY 1500mm

Date: 12-11-2024



## Technical data

tab terminal with earth symbol  
 Flachstecker mit Erdungsfahne  
 DIN 46244-A 6,3-0,8 St

DIN 46244-A 6,3-0,8 St

8.11

53.11

1.5

16.7

42

teflon insulation sleeve green  
 Teflon Isolierschlauch grün  
 1450.00 mm length/lang

1460\*100 mm length/lang

F-1792  
 with or without notch approved  
 mit oder ohne Kerbe zulässig

0.4

B=66 ±0.5

A=100 ±0.5

reset button  
 threaded bushing  
 Rückstellknopf  
 in Gewindebohrung

bushing made  
 of plastic  
 Gewindebuchse  
 aus Kunststoff

M10x1

20.3

34.8

wiring diagram / Schaltschema

NC-contact / NC-Kontakt

12

11

MONOPHASE	MONOFASE/MONOPHASE
NUMBER OF POLES	POLI/POLES=2
MAXIMUM TEMPERATURE °	T max=230°
WIRE mm	L=1500mm
PROBE DIAMETER MM	B=4mm
PROBE LENGTH MM	A=116mm

## Manufacturer code

E.G.O. ELEKTRO GERATE AG

