

1106749

SAFETY THERMOSTAT 230° SINGLE PHASE 0,5A - SENSOR Ø 4X116mm CAPILLARY 1500mm

Date: 23-11-2024



Technical data

<p>tab terminal with earth symbol Flachstecker mit Erdungsfahne DIN 46244-A 6,3-0,8 St</p> <p>DIN 46244-A 6,3-0,8 St</p> <p>8.1</p> <p>53.1</p> <p>1.5</p> <p>16.7</p> <p>42</p>	<table border="1"> <tr> <td>MONOPHASE</td> <td>MONOFASE/MONOPHASE</td> </tr> <tr> <td>NUMBER OF POLES</td> <td>POLI/POLES=2</td> </tr> <tr> <td>MAXIMUM TEMPERATURE °</td> <td>T max=230°</td> </tr> <tr> <td>WIRE mm</td> <td>L=1500mm</td> </tr> <tr> <td>PROBE DIAMETER MM</td> <td>B=4mm</td> </tr> <tr> <td>PROBE LENGTH MM</td> <td>A=116mm</td> </tr> </table>	MONOPHASE	MONOFASE/MONOPHASE	NUMBER OF POLES	POLI/POLES=2	MAXIMUM TEMPERATURE °	T max=230°	WIRE mm	L=1500mm	PROBE DIAMETER MM	B=4mm	PROBE LENGTH MM	A=116mm	<p>reset button threaded bushing Rückstellknopf in Gewindebohrung</p> <p>bushing made of plastic Gewindebuchse aus Kunststoff</p> <p>25.4</p> <p>20</p> <p>M10x1</p> <p>20.3</p> <p>34.8</p>
MONOPHASE	MONOFASE/MONOPHASE													
NUMBER OF POLES	POLI/POLES=2													
MAXIMUM TEMPERATURE °	T max=230°													
WIRE mm	L=1500mm													
PROBE DIAMETER MM	B=4mm													
PROBE LENGTH MM	A=116mm													
<p>teflon insulation sleeve green Teflon Isolierschlauch grün 1450_{±0.05} mm length/lang</p> <p>1460⁺¹⁰⁰ mm length/lang</p> <p>F-1792 with or without notch approved mit oder ohne Kerbe zulässig</p> <p>B=66_{±0.5}</p> <p>A=100_{±0.5}</p> <p>0.4</p>	<p>wiring diagram / Schaltschema</p>													

Manufacturer code

E.G.O. ELEKTRO GERATE AG

