

1106405

THERMOSTAT 182°C - PROBE Ø 6X130 mm

Date: 13-04-2025



ORIGINAL
OSP
SPARE PARTS

Technical data

Technical drawing showing the thermostat probe assembly with dimensions and component labels:

- Dimensions: 38, 43.5, 32, 35, 28 ±0.25, 45, 10.5, 10, 4.6 ±0.2, 23 ±0.3, 870 ±0.50, 6.3 ±0.05, 2.0 ±0.05.
- Labels: Teflon Isolierschlauch/Guida in Teflon 750-60 mm lang/lunghezza; Stopfbuchsippel/Prestoppa 0000 615.327; Scheibe/Ranella 2x 00067.055.02; Dichtung/Guarritazione 0000 624.043; Düse/Fori di fissaggio M4; Einschraubtiefe für Befestigungsschrauben/ Penetrazione massima delle viti di fissaggio max. 4mm; Schaltschere/Scheta elettrica.
- Reference: DIN 46244-A 6.3-08-SI.

| | |
|-----------------------|--------------------|
| MONOPHASE | MONOFASE/MONOPHASE |
| NUMBER OF POLES | POLI/POLES=2 |
| MINIMUM TEMPERATURE ° | T min=95° |
| MAXIMUM TEMPERATURE ° | T max=182° |
| WIRE mm | L=900mm |
| PROBE DIAMETER MM | B=6mm |
| PROBE LENGHT MM | A=130mm |
| STUFFING BOX MM | M9X1 |
| SHAFT mm | ALBERO/SHAFT=4X6mm |

Kann bei Anschlag links auch geschlossen sein/ Quando il perno è in posizione «1» il contatto può risultare chiuso

Manufacturer code

| |
|--------------------------|
| LOTUS SPA |
| E.G.O. ELEKTRO GERATE AG |
| LOTUS SPA |

| |
|-------------------------------------|
| E.G.O. ELEKTRO GERATE AG |
| POLARIS ALI GROUP SRL A SOCIO UNICO |
| LOTUS SPA |