

1106729

# THERMOSTAT 105-190° 230V SINGLE PHASE- SENSOR Ø 4X235mm - CAPILLARY 1500mm

Date: 23-12-2024



**ORIGINAL  
OSP  
SPARE PARTS**

## Technical data

<p>MONOPHASE</p> <p>NUMBER OF POLES</p> <p>MINIMUM TEMPERATURE °</p> <p>MAXIMUM TEMPERATURE °</p> <p>WIRE mm</p> <p>PROBE DIAMETER MM</p> <p>PROBE LENGTH MM</p> <p>STUFFING BOX MM</p> <p>SHAFT mm</p> <p>                 Teflon Isolierschlauch, grau Teflon insulation sleeve, grey/ Guaina in Teflon, grigio 1250,80 mm lang/length/lunghezza                  Stopfbuchsippel Stuffing gland nipple/ Prestistoppa 0000 615,319                  Scheibe Disc/ Ranella 2x 00067,055,11                  Dichtung Sealing/ Guarnizione 0000 624,043                  Düse/Nozzle/Fori di fissaggio M4 Einschraubtiefe für Befestigungsschrauben/ screw-in depth for fixing/ Penetrazione massima delle viti di fissaggio max. 4mm.                  DN 46244-A 6.3-0.8-St versilbert/silver-plated/argento             </p>	MONOPHASE	MONOFASE/MONOPHASE
	NUMBER OF POLES	POLI/POLES=2
	MINIMUM TEMPERATURE °	T min=105°
	MAXIMUM TEMPERATURE °	T max=190°
	WIRE mm	L=1500mm
	PROBE DIAMETER MM	B=4mm
	PROBE LENGTH MM	A=235mm
	STUFFING BOX MM	M10X1
SHAFT mm	ALBERO/SHAFT=4X6mm	

Kann bei Anschlag links auch geschlossen sein/ Can also be closed in off-position/ Quando il perno è in posizione 0° il contatto può risultare chiuso

Schaltzeichen/  
Wiring diagram/  
Schema elettrico

## Manufacturer code

ELFRAMO SPA

ELFRAMO SPA

E.G.O. ELEKTRO GERATE AG

E.G.O. ELEKTRO GERATE AG