

1106228

THERMOSTAT 62-189°C SINGLE PHASE EGO 55.19632.030 - PROBE Ø 4X120mm CAPILLARY 700mm

Date: 22-01-2025



**ORIGINAL
OSP
SPARE PARTS**

Technical data

Duse/Fori di fissaggio M4.
Einschraubtiefe für
Befestigungsschrauben/
Penetrazione massima
delle viti di fissaggio
max. 4mm.

Fühler/bulbo 00055.554.50

Teflon-Isolierschlauch, grau
Guaina in Teflon, grigio
700 40 mm lang/lunghezza

Aufsetzschalter/
commutatore ausiliario
0055.045.001

DIN 46244-A-6.3-0.8-Ms
versilberl/argentato

MONOPHASE	MONOFASE/MONOPHASE
NUMBER OF POLES	POLI TERMOSTATO/THERMOSTAT POLES=2
MINIMUM TEMPERATURE °	T min=62°
MAXIMUM TEMPERATURE	T max=189°
WIRE mm	L=700mm
PROBE DIAMETER MM	B=4mm
PROBE LENGTH MM	A=120mm
NUMBER OF POLES	POLI INTERRUTTORE/SWITCH POLES=4

Aus/SPE...
30°...
Aus/SPE... ENACESSO P6 - 6
Schaltleistung Aufsetzschalter/
Schena elettrico...
Prüfklasse/Classe Callaudo I = 10 000 Zyklen/Cicli
Max. Gehäusetemperatur/Max. temp. circonferenz 120°C

Schaltschema/
Schema elettrico

Manufacturer code

SILKO ALI GROUP SRL A SOCIO UNICO

MARENO ALI GROUP SRL A SOCIO UNICO
MARENO ALI GROUP SRL A SOCIO UNICO
E.G.O. ELEKTRO GERATE AG