

1106290

THERMOSTAT 232°C THREEPHASE SAFETY - SENSOR Ø 6X94 mm CAPILLARY 900mm

Date: 06-04-2025



Technical data

Technical drawing details:

- Terlan Isolierschlauch typisch / Terlan insulation sleeve typical: 700 mm long/length
- Stiftbuchsenkopf / Stuffing gland nipple: 0000 65.319
- Scheibe / Disc: 2x 00067.055.11
- Dichtung / Sealing: 0000 624.043
- 890-08 mm long/length
- F-8523: Mit oder ohne Kerbe zulässig / With or without notch approved
- B=59 mm
- A=58 mm
- Rücksetzknopf / Reset button: 35 mm, 28.4 mm
- Düsen / Nozzle: 14 mm
- 533 mm
- DN 68244-6.3-2.8-74

THREE PHASE	TRIFASE/THREE PHASE
NUMBER OF POLES	POLI/POLES=6
MAXIMUM TEMPERATURE °C	T max=232°
WIRE mm	L=900mm
PROBE DIAMETER MM	B=6mm
PROBE LENGHT MM	A=94mm
STUFFING BOX MM	M10X1

Manufacturer code

MODULAR PROFESSIONAL SRL
GIORIK SPA
GIORIK SPA
E.G.O. ELEKTRO GERATE AG

MBM- EUROTEC SRL -

E.G.O. ELEKTRO GERATE AG

GIORIK SPA

E.G.O. ELEKTRO GERATE AG

E.G.O. ELEKTRO GERATE AG
