

1106729

THERMOSTAT 105-190° 230V SINGLE PHASE- SENSOR Ø 4X235mm - CAPILLARY 1500mm

Date: 23-12-2024



**ORIGINAL
OSP
SPARE PARTS**

Technical data

<p>MONOPHASE</p> <p>NUMBER OF POLES</p> <p>MINIMUM TEMPERATURE °</p> <p>MAXIMUM TEMPERATURE °</p> <p>WIRE mm</p> <p>PROBE DIAMETER MM</p> <p>PROBE LENGTH MM</p> <p>STUFFING BOX MM</p> <p>SHAFT mm</p> <p>4.6 ±0.1</p> <p>1470 ±100 mm</p> <p>Ø 6</p> <p>F-2047</p> <p>1250 ±80 mm</p> <p>M 10 x 1</p> <p>38</p> <p>37</p> <p>43.5 ±0.1</p> <p>4.1 mm Hub/Hubsposstano del/glia 360° ±0.1</p> <p>23 ±0.5</p> <p>35</p> <p>28 ±0.25</p> <p>48 ±0.1</p> <p>10.5</p> <p>48 ±0.1</p> <p>10.5</p> <p>DN 46244-A 6.3-0.8-St versilber/silver-plated/argento</p> <p>Teflon Isolierschlauch, grau Teflon insulation sleeve, grey/ Guaina in Teflon, grigio 1250 ±80 mm lang/length/lunghezza</p> <p>Stopfbuchse Stuffing gland nipple/ Prestitoppa 0000 615.319</p> <p>Scheibe Disc/ Ranella 2x 00067.055.11</p> <p>Dichtung Sealing/ Guarnizione 0000 624.043</p> <p>Düse/Nozle/Fori di fissaggio M4 Einschraubtiefe für Befestigungsschrauben/ screw-in depth for fixing/ Penetrazione massima delle viti di fissaggio max. 4mm.</p> <p>Kann bei Anschlag links auch geschlossen sein/ Can also be closed in off-position/ Quando il perno è in posizione 0° il contatto può risultare chiuso</p> <p>Schaltzeichen/ Wiring diagram/ Schema elettrico</p>	MONOPHASE	MONOFASE/MONOPHASE
	NUMBER OF POLES	POLI/POLES=2
	MINIMUM TEMPERATURE °	T min=105°
	MAXIMUM TEMPERATURE °	T max=190°
	WIRE mm	L=1500mm
	PROBE DIAMETER MM	B=4mm
	PROBE LENGTH MM	A=235mm
	STUFFING BOX MM	M10X1
SHAFT mm	ALBERO/SHAFT=4X6mm	

Manufacturer code

ELFRAMO SPA

ELFRAMO SPA
E.G.O. ELEKTRO GERATE AG
E.G.O. ELEKTRO GERATE AG