

1106749

SAFETY THERMOSTAT 230° SINGLE PHASE 0,5A - SENSOR Ø 4X116mm CAPILLARY 1500mm

Date: 22-01-2025



Technical data

tab terminal with earth symbol
 Flachstecker mit Erdungsfahne
 DIN 46244-A 6,3-0,8 St

DIN 46244-A 6,3-0,8 St

42

16,7

53 ± 0,1

8 ± 0,1

1,5

1460⁺¹⁰⁰ mm length/lang

1450⁺⁹⁰ mm length/lang

teflon insulation sleeve green
 Teflon Isolierschlauch grün

F-1792
 with or without notch approved
 mit oder ohne Kerbe zulässig

B=66 ± 0,5

A=100 ± 0,5

0,4

reset button
 threaded bushing
 Rückstellknopf
 in Gewindebohrung

bushing made
 of plastic
 Gewindebuchse
 aus Kunststoff

M10x1

20,3

34,8

wiring diagram / Schaltschema

NC-contact / NC-Kontakt

12

11

MONOPHASE	MONOFASE/MONOPHASE
NUMBER OF POLES	POLI/POLES=2
MAXIMUM TEMPERATURE °	T max=230°
WIRE mm	L=1500mm
PROBE DIAMETER MM	B=4mm
PROBE LENGTH MM	A=116mm

Manufacturer code

E.G.O. ELEKTRO GERATE AG

