

1106749

SAFETY THERMOSTAT 230° SINGLE PHASE 0,5A - SENSOR Ø 4X116mm CAPILLARY 1500mm

Date: 22-11-2024



Technical data

tab terminal with earth symbol
 Flachstecker mit Erdungsfahne
 DIN 46244-A 6,3-0,8 St

DIN 46244-A 6,3-0,8 St

42

53.1

16.7

1.5

teflon insulation sleeve green
 Teflon Isolierschlauch grün
 1450.00 mm length/lang

1460*100 mm length/lang

F-1792
 with or without notch approved
 mit oder ohne Kerbe zulässig

4

MONOPHASE	MONOFASE/MONOPHASE
NUMBER OF POLES	POLI/POLES=2
MAXIMUM TEMPERATURE °	T max=230°
WIRE mm	L=1500mm
PROBE DIAMETER MM	B=4mm
PROBE LENGTH MM	A=116mm

reset button threaded bushing
 Rückstellknopf in Gewindebohrung

bushing made of plastic
 Gewindebuchse aus Kunststoff

25.4

20.3

M10x1

34.8

wiring diagram / Schaltschema

NC-contact / NC-Kontakt

12

11

Manufacturer code

E.G.O. ELEKTRO GERATE AG

