

1106749

SAFETY THERMOSTAT 230° SINGLE PHASE 0,5A - SENSOR Ø 4X116mm CAPILLARY 1500mm

Date: 07-04-2025



Technical data

<p>tab terminal with earth symbol Flachstecker mit Erdungsfahne DIN 46244-A 6,3-0,8-St</p> <p>DIN 46244-A 6,3-0,8 St</p> <p>8,8 ±1</p> <p>53 ±1</p> <p>1,5</p> <p>16,7</p> <p>42</p>	<p>MONOPHASE</p> <p>NUMBER OF POLES</p> <p>MAXIMUM TEMPERATURE</p> <p>WIRE mm</p> <p>PROBE DIAMETER MM</p> <p>PROBE LENGHT MM</p>	<p>MONOFASE/MONOPHASE</p> <p>POLI/POLES=2</p> <p>T max=230°</p> <p>L=1500mm</p> <p>B=4mm</p> <p>A=116mm</p>
<p>reset button threaded bushing Rückstellknopf in Gewindebohrung</p> <p>bushing made of plastic Gewindebuchse aus Kunststoff</p> <p>teflon insulation sleeve green Teflon Isolierschlauch grün 1450_{±0} mm length/lang</p> <p>1460⁺¹⁰⁰ mm length/lang</p> <p>F-1792 with or without notch approved mit oder ohne Kerbe zulässig</p> <p>B=66 ±s</p> <p>A=100 ±s</p> <p>0,4</p> <p>wiring diagram / Schaltschema</p> <p>NC-contact / NC-Kontakte</p>	<p>25,4</p> <p>20,3</p> <p>34,8</p>	

Manufacturer code

E.G.O. ELEKTRO GERATE AG

