

1106749

TERMOSTATO 230°C MONOFASE SICUREZZA 0,5 A - SENSORE Ø 4X116mm CAPILLARE 1500mm

Data: 23-02-2025



Dati tecnici

tab terminal with earth symbol
 Flachstecker mit Erdungsfahne
 DIN 46244-A 6,3-0,8 St

DIN 46244-A 6,3-0,8 St

8.11

53.11

1.5

16.7

42

reset button
 threaded bus
 Rückstellknopf
 in Gewindebühse

bushing made
 of plastic
 Gewindebühse
 aus Kunststoff

M10x1

20.3

34.8

teflon insulation sleeve green
 Teflon Isolierschlauch grün
 1450_{±0.05} mm length/lang

F-1792
 with or without notch approved
 mit oder ohne Kerbe zulässig

1460⁺¹⁰⁰ mm length/lang

B=66_{±0.5}

A=100_{±0.5}

0.4

wiring diagram / Schaltschema

NC-contact / NC-Kontakt

12

11

MONOFASE	MONOFASE/MONOPHASE
NUMERO POLI	POLI/POLES=2
TEMPERATURA MASSIMA °	T max=230°
CAPILLARE mm	L=1500mm
SENSORE DIAMETRO MM	B=4mm
SENSORE LUNGHEZZA MM	A=116mm

Codici produttore

E.G.O. ELEKTRO GERATE AG

