

1106749

# TERMOSTATO 230°C MONOFASE SICUREZZA 0,5 A - SENSORE Ø 4X116mm CAPILLARE 1500mm

Data: 19-09-2024



## Dati tecnici

tab terminal with earth symbol  
 Flachstecker mit Erdungsfahne  
 DIN 46244-A 6,3-0,8 St

DIN 46244-A 6,3-0,8 St

8.11

53.11

1.5

16.7

42

reset button  
 threaded bus  
 Rückstellknopf  
 in Gewindebuchse

bushing made  
 of plastic  
 Gewindebuchse  
 aus Kunststoff

M10x1

20.3

34.8

teflon insulation sleeve green  
 Teflon Isolierschlauch grün  
 1450<sub>±0.05</sub> mm length/lang

F-1792  
 with or without notch approved  
 mit oder ohne Kerbe zulässig

1460<sup>+100</sup> mm length/lang

B=66<sub>±0.5</sub>

A=100<sub>±0.5</sub>

0.4

wiring diagram / Schaltschema

NC-contact / NC-Kontakt

12

11

MONOFASE	MONOFASE/MONOPHASE
NUMERO POLI	POLI/POLES=2
TEMPERATURA MASSIMA °	T max=230°
CAPILLARE mm	L=1500mm
SENSORE DIAMETRO MM	B=4mm
SENSORE LUNGHEZZA MM	A=116mm